

Compact series Electric Chain Hoist 1Ton to 5Ton

Technical Parameters

Single Speed				Lifting Motor		Power Supply			Travelling Motor		Control Voltage (V)
Model	Capacity (Ton)	Lifting Speed (m/min)	Chain Falls	Power (KW)	Rotation Speed (r/min)	Phase	Voltage (V)	Frequency (Hz)	Power (KW)	Rotation Speed (r/min)	
HHBDC0.5-01	0.5	7	1	0.5	2800	3	200V-690V	50/60	-	-	24,36,48
HHBDC01-01	1	4.6	1	1.1	1440	3	200V-690V	50/60	-	-	24,36,48
HHBDC02-02	2	2.3	2	1.1	1440	3	200V-690V	50/60	-	-	24,36,48
HHBDC03-03	3	1.6	3	1.1	1440	3	200V-690V	50/60	-	-	24,36,48
HHBDC05-05	5	0.9	5	1.1	1440	3	200V-690V	50/60	-	-	24,36,48

Size Specification		Unit(mm)							
Type	Capacity (Ton)	A	B	C	D	E	Z	G	Chain
HHBDC01-01	1	216	216	135	170	680	530	31	Ø7.1
HHBDC02-02	2	216	216	90	215	705	645	26	Ø7.1
HHBDC03-03	3	216	216	125	270	900	800	42	Ø7.1
HHBDC05-05	5	216	216	175	340	1000	895	48	Ø7.1