












Endless flat webbing sling

Technical Parameters

Colour	Colour coded according	Working Load Limit with 1 webbing sling							Working Load Limit with 2 webbing sling			
		Straight lift	Choked lift	ø					Straight 45°	Choked lift up to 45°	Straight lift 45-60°	Choked lift 45-60°
0-7	7-45			45-60	Up to 45	45-60						
-	-	-	-	0-7	7-45	45-60	Up to 45	45-60	-	-	-	-
-	-											
-	-	1.0	0.8	2.0	1.4	1.0	0.7	0.5	1.4	1.12	1.0	0.8
Purple	WLL 1T	1.000	800	2.000	1.400	1.000	700	500	1.400	1.120	1.000	800
Green	WLL 2T	2.000	1.600	4.000	2.800	2.000	1.400	1.000	2.800	2.240	2.000	1.600
Yellow	WLL 3T	3.000	2.400	6.000	4.200	3.000	2.100	1.500	4.200	3.360	3.000	2.400
Grey	WLL 4T	4.000	3.200	8.000	5.600	4.000	2.800	2.000	5.600	4.480	4.000	3.200
Red	WLL 5T	5.000	4.000	10.000	7.000	5.000	3.500	2.500	7.000	5.600	5.000	4.000
Brown	WLL 6T	6.000	4.800	12.000	8.400	6.000	4.200	3.000	8.400	6.720	6.000	4.800
Blue	WLL 8T	8.000	6.400	16.000	11.200	8.000	5.600	4.000	11.200	8.960	8.000	6.400
Orange	WLL 10T	10.000	8.000	20.000	14.000	10.000	7.000	5.000	14.000	11.000	10.000	8.000
Orange	WLL 20T	20.000	16.000	40.000	28.000	20.000	14.000	10.000	28.000	22.400	20.000	16.000